

CP60 COMPOSITE HOSE



- Safely and reliably convey water AND oil
- For both suction & discharge applications
- Excellent resistance to kinking or crushing
- All assemblies tested to 1.5 x working pressure

CP60 Oil & Water Suction & Discharge Hose

BULK

Part Number	ID	Max WP	Vacuum Inches	Min BR	Weight	Standard Pack
	in	psi	Hg	in	lbs/ft	
CP60-400	4	200	26	16.0	3.50	65'
CP60-600	6	200	26	23.0	7.70	65'
CP60-800	8	200	26	32.0	12.00	65'
CP60-1000	10	200	26	40.0	16.90	40'
CP60-1000	12	200	26	47.0	19.80	40'

ASSEMBLIES - FIXED X FLOATING

Part Number	Hose Size	Length	Fitting A	Fitting B	Weight / Assy
		ft			lbs
CP60-400FFL-10	4	10	Fixed 150lb	Floating 150lb	70.6
CP60-400FFL-20	4	20	Fixed 150lb	Floating 150lb	99.2
CP60-600FFL-10	6	10	Fixed 150lb	Floating 150lb	160.9
CP60-600FFL-20	6	20	Fixed 150lb	Floating 150lb	233.7
CP60-800FFL-10	8	10	Fixed 150lb	Floating 150lb	264.6
CP60-800FFL-20	8	20	Fixed 150lb	Floating 150lb	381.4
CP60-1000FFL-10	10	10	Fixed 150lb	Floating 150lb	363.8
CP60-1000FFL-20	10	20	Fixed 150lb	Floating 150lb	507.1
CP60-1200FFL-10	12	10	Fixed 150lb	Floating 150lb	551.3
CP60-1200FFL-20	12	20	Fixed 150lb	Floating 150lb	760.0

*Assembled with fixed x floating carbon steel 150lbs ANSI flanges

CP60 COMPOSITE ASSEMBLIES - Vic x Vic

Part Number	Hose Size	Length	Fitting A	Fitting B	Weight / Assy
		ft			lbs
CP60-800GG-10	8	10	Vic	Vic	178.57
CP60-800GG-20	8	20	Vic	Vic	284.40
CP60-1000GG-10	10	10	Vic	Vic	291.01
CP60-1000GG-20	10	20	Vic	Vic	423.29
CP60-1200GG-10	12	10	Vic	Vic	341.72
CP60-1200GG-20	12	20	Vic	Vic	465.18

